

## Datasheet for: RX033

### Product Type: 110v portable Tool transformers

3kVA 230V to 2x110V Isolating Tool Transformer



|                    |   |
|--------------------|---|
| VA                 | 3000  |
| Input Voltage      | 230   |
| Input Termination  | Mains lead with UK 13amp plug   |
| Input Current      | 14  |
| Output Voltage     | 110   |
| Output Notes       | N.B. Intermittent tool rating is the maximum rating for operating load at 25% duty cycle, i.e. 5 mins on / 15 mins off. |
| Output Termination | Two 16amp Yellow sockets  |
| Product Case       | 701 Tough GRP case with carrying handle IP44  |
| Dimension          | Ht:280 W:200 D:200  |
| Weight             | 18kg  |
| Primary Protection | Push to reset circuit breaker   |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-06 CE & RoHS   |
| Standard           | IP44  |
| Notes              | IP44 Tool transformer for intermittent use  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product RX033 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
14/03/2025

