

Datasheet for: RX033

Product Type: 110v portable Tool transformers

3kVA 230V to 2x110V Isolating Tool Transformer



VA	3000
Input Voltage	230
Input Termination	Mains lead with UK 13amp plug
Input Current	14
Output Voltage	110
Output Notes	N.B. Intermittent tool rating is the maximum rating for operating load at 25% duty cycle, i.e. 5 mins on / 15 mins off.
Output Termination	Two 16amp Yellow sockets
Product Case	701 Tough GRP case with carrying handle IP44
Dimension	Ht:280 W:200 D:200
Weight	18kg
Primary Protection	Push to reset circuit breaker
Product Type	Safety Isolating transformer Conforms to EN61558-2-06 CE & RoHS
Standard	IP44
Notes	IP44 Tool transformer for intermittent use

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product RX033 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
04/04/2026



