



## Datasheet for: ST1000

### Product Type: 110v portable Tool transformers

1000VA 230v to 110v tool transformer

VA	1000
Input Voltage	230
Input Termination	Mains lead with UK 13amp plug
Input Current	4
amps	9
Output Voltage	110
Output Notes	N.B. Intermittent tool rating is the maximum rating for operating load at 25% duty cycle, i.e. 5 mins on / 15 mins off.
Output Termination	Single 16amp Yellow sockets
Product Case	601 Tough GRP case with carrying handle IP44
Dimension	Ht:210 W:165 D:165
Weight	7kg
Primary Protection	Push to reset circuit breaker SP3
Surge Protection	SL15 Surge Limiter
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Notes	IP44 Tool transformer for intermittent use British Built

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product ST1000 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
14/03/2025



