



## Datasheet for: ST1000

### Product Type: 110v portable Tool transformers

1000VA 230v to 110v tool transformer

|                    |   |
|--------------------|---|
| VA                 | 1000  |
| Input Voltage      | 230   |
| Input Termination  | Mains lead with UK 13amp plug   |
| Input Current      | 4   |
| amps               | 9   |
| Output Voltage     | 110   |
| Output Notes       | N.B. Intermittent tool rating is the maximum rating for operating load at 25% duty cycle, i.e. 5 mins on / 15 mins off. |
| Output Termination | Single 16amp Yellow sockets   |
| Product Case       | 601 Tough GRP case with carrying handle IP44  |
| Dimension          | Ht:210 W:165 D:165  |
| Weight             | 7kg   |
| Primary Protection | Push to reset circuit breaker SP3   |
| Surge Protection   | SL15 Surge Limiter  |
| Product Type       | Safety Isolating transformer  |
| Standard           | Conforms to EN61558-2-6 CE & RoHS   |
| Notes              | IP44 Tool transformer for intermittent use British Built  |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product ST1000 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
22/12/2024



