

Datasheet for: ST15002

Product Type: 110v portable Tool

transformers

1500VA 230v to 2 x 110v CTE Tool Transformer

VA 1500 Input Voltage 230

Input Termination Mains lead with UK 13amp plug

Input Current 6.5 amps 13.6 Output Voltage 110

Output Notes N.B. Intermittent tool rating is the maximum rating for operating load at 25% duty cycle, i.e. 5 mins on / 15 mins off.

Output Termination Two 110V 16amp Yellow Sockets

Product Case 701 Tough GRP case with carrying handle IP44

Dimension Ht:280 W:200 D:200

Weight 10kg

Primary Protection Push to reset circuit breaker SP8

Surge Protection SL32 Surge Limiter

Product Type Safety Isolating transformer

Standard IP44. Conforms to EN61558-2-06 CE & RoHS

Notes IP44 Tool transformer for intermittent use British Built

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)









Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 28/11/2025



