

Datasheet for: ST15002

Product Type: 110v portable Tool transformers

1500VA 230v to 2 x 110v CTE Tool Transformer

VA	1500
Input Voltage	230
Input Termination	Mains lead with UK 13amp plug
Input Current	6.5
amps	13.6
Output Voltage	110
Output Notes	N.B. Intermittent tool rating is the maximum rating for operating load at 25% duty cycle, i.e. 5 mins on / 15 mins off.
Output Termination	Two 110V 16amp Yellow Sockets
Product Case	701 Tough GRP case with carrying handle IP44
Dimension	Ht:280 W:200 D:200
Weight	10kg
Primary Protection	Push to reset circuit breaker SP8
Surge Protection	SL32 Surge Limiter
Product Type	Safety Isolating transformer
Standard	IP44. Conforms to EN61558-2-06 CE & RoHS
Notes	IP44 Tool transformer for intermittent use British Built



Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product ST15002 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
20/12/2025



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com