

## Datasheet for: SV1024

### Product Type: Low voltage portable Tool transformers

400VA 110v to 24v site transformer with sockets



VA	400
Input Voltage	110
Input Termination	Mains lead with Yellow 16amp plug
Input Current	3.636363636363636
amps	16
Output Voltage	24
Output Notes	400va continuous rating
Output Termination	Single 16amp Purple sockets
Product Case	601 Tought GRP case with carrying handle IP44
Dimension	Ht:210 W:165 D:165
Weight	6kg
Primary Protection	Push to reset circuit breaker SP3
Surge Protection	SL15 Surge Limitor
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.

07/02/2023


