

Datasheet for: 3PAD0060

Product Type: 3P+PE Auto Delta Delta

5000VA 3P 415-230 Delta Delta Autowound



VA	5000
Input Voltage	415
Input Termination	Screw terminals
Input Current	6.96
amps	12.55
Output Voltage	230
Output Notes	Line to Line 230v Line to Neutral 132v
Output Termination	Screw terminals
Product Case	P4 Industrial floor/wall mounting case IP23
Dimension	Ht:270 W:215 L:338
Weight	25kg
Surge Protection	SL32 Surge Limitor
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PAD0060 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/02/2025

