

## Datasheet for: 3PAS0210

### Product Type: 3P+N Auto Star Star

20kVA 3P+N 415 - 220V Autowound Hardwired



|                    |   |
|--------------------|---|
| VA                 | 20000                                       |
| Input Voltage      | 415   |
| Input Termination  | Terminal Posts                              |
| Input Current      | 27.86                                       |
| amps               | 52.55                                       |
| Output Voltage     | 220   |
| Output Notes       | Line to Line 220V Line to Neutral 127V      |
| Output Termination | Terminal Posts                              |
| Product Case       | P7 Industrial floor/wall mounting case IP23 |
| Dimension          | Ht:480 W:334 L:438                          |
| Weight             | 74kg  |
| Surge Protection   | MS35 Surge Limiter                          |
| Product Type       | Autowound transformer                       |
| Standard           | Conforms to EN61558-2-13 CE & RoHS          |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PAS0210 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
23/02/2025

