

Datasheet for: 3PAS0210

Product Type: 3P+N Auto Star Star

20kVA 3P+N 415 - 220V Autowound Hardwired



| | |
|--------------------|---|
| VA | 20000 |
| Input Voltage | 415 |
| Input Termination | Terminal Posts |
| Input Current | 27.86 |
| amps | 52.55 |
| Output Voltage | 220 |
| Output Notes | Line to Line 220V Line to Neutral 127V |
| Output Termination | Terminal Posts |
| Product Case | P7 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:480 W:334 L:438 |
| Weight | 74kg |
| Surge Protection | MS35 Surge Limiter |
| Product Type | Autowound transformer |
| Standard | Conforms to EN61558-2-13 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PAS0210 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/01/2025

