

## Datasheet for: 3PTS05449

### Product Type: 3P+N Isolating Delta Star

5kva 3P Delta Star 480v to 400v Hardwired



VA	5000
Input Voltage	480
Input Termination	3 way screw terminals
Input Current	3.5
amps	7.25
Output Voltage	400
Output Notes	Line to Line 400v Line to neutral 230vac
Output Termination	3 way screw terminals
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	21kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	5.5%

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS05449 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
06/05/2026



