

Datasheet for: 3PTS16319

Product Type: 3P+N Isolating Delta Star

15kva 3P Delta Star 415v to 208v Hardwired



VA	15000
Input Voltage	415
Input Termination	M6 Brass studs
Input Current	20.83
amps	41.66
Output Voltage	208
Output Notes	Line to Line 208v Line to Neutral 120v
Output Termination	M6 Brass studs
Product Case	T3 Industrial floor/wall mounting case IP23
Dimension	Ht:500 L: 525 W:450 (mm)
Weight	95kg
Surge Protection	MS35 Surge Limiters
Product Type	Isolating transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Regulation	2.00%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PTS16319 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 09/02/2025



