

**Datasheet for: 3PTS42734**

**Product Type: 3P+N Isolating Delta Star**

40Kva 3P+N Delta Star 415V to 380V Hardwired



|                    |   |
|--------------------|---|
| VA                 | 40000                                       |
| Input Voltage      | 415   |
| Input Termination  | M8 Brass studs                              |
| Input Current      | 55.55                                       |
| amps               | 60.61                                       |
| Output Voltage     | 380   |
| Output Notes       | Line to Line 380v Line to Neutral 220v      |
| Output Termination | M8 Brass studs                              |
| Product Case       | T4 Industrial floor/wall mounting case IP23 |
| Dimension          | Ht:600 L: 625 W:500 (mm)                    |
| Weight             | 265kg                                       |
| Surge Protection   | MS35 Surge Limiters x 6                     |
| Product Type       | Isolating transformer                       |
| Standard           | Conforms to EN61558-2-23 CE & RoHS          |
| Regulation         | 3.0%  |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS42734 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 03/04/2025



*[Handwritten signature]*

