

Datasheet for: 3PTS42734

Product Type: 3P+N Isolating Delta Star

40Kva 3P+N Delta Star 415V to 380V Hardwired



VA 40000 Input Voltage 415

Input Termination M8 Brass studs

Input Current 55.55 amps 60.61 Output Voltage 380

Output Notes Line to Line 380v Line to Neutral 220v

Output Termination M8 Brass studs

Product Case T4 Industrial floor/wall mounting case IP23

Dimension Ht:600 L: 625 W:500 (mm)

Weight 265kg

Surge Protection MS35 Surge Limiters x 6
Product Type Isolating transformer

Standard Conforms to EN61558-2-23 CE & RoHS

Regulation 3.0%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PTS42734 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

15/12/2025

