

**Datasheet for: 3PAD0069**

**Product Type: 3P+PE Auto Delta Delta**

5000VA 3P 415-220V Hardwired



|                    |   |
|--------------------|---|
| VA                 | 5000  |
| Input Voltage      | 415   |
| Input Termination  | Terminal Posts                              |
| Input Current      | 7   |
| amps               | 13.2  |
| Output Voltage     | 220   |
| Output Termination | Terminal Posts                              |
| Product Case       | P4 Industrial floor/wall mounting case IP23 |
| Dimension          | Ht:270 W:215 L:338                          |
| Weight             | 14kg  |
| Surge Protection   | SL32 Surge Limiters                         |
| Product Type       | Autowound transformer                       |
| Standard           | Conforms to EN61558-2-13 CE & RoHS          |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.

07/02/2023  
  
