

**Datasheet for: 3PAD0119**

**Product Type: 3P+PE Auto Delta Delta**

7.5kVA 3P 415-220V Hardwired



|                    |   |
|--------------------|---|
| VA                 | 7500  |
| Input Voltage      | 415   |
| Input Termination  | Terminal Posts                              |
| Input Current      | 18  |
| amps               | 34  |
| Output Voltage     | 220   |
| Output Termination | Terminal Posts                              |
| Product Case       | P6 Industrial floor/wall mounting case IP23 |
| Dimension          | H:454, L:384, W:305                         |
| Weight             | 22kg  |
| Surge Protection   | SL32 Surge Limiters                         |
| Product Type       | Autowound transformer                       |
| Standard           | Conforms to EN61558-2-13 CE & RoHS          |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PAD0119 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 23/02/2025

