

Datasheet for: 3PAD0119

Product Type: 3P+PE Auto Delta Delta

7.5kVA 3P 415-220V Hardwired



| | |
|--------------------|---|
| VA | 7500 |
| Input Voltage | 415 |
| Input Termination | Terminal Posts |
| Input Current | 18 |
| amps | 34 |
| Output Voltage | 220 |
| Output Termination | Terminal Posts |
| Product Case | P6 Industrial floor/wall mounting case IP23 |
| Dimension | H:454, L:384, W:305 |
| Weight | 22kg |
| Surge Protection | SL32 Surge Limiters |
| Product Type | Autowound transformer |
| Standard | Conforms to EN61558-2-13 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PAD0119 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
25/05/2026



