

Datasheet for: 3PAD0227

Product Type: 3P+PE Auto Delta Delta

20kVA 3Phase 400-208v Delta/Delta + PE Hardwired



VA	20000
Input Voltage	400
Input Termination	Screw terminals
Input Current	28.88
amps	55.52
Output Voltage	208
Output Termination	Screw terminals
Product Case	P7 Industrial floor/wall mounting case IP23
Dimension	Ht:480 W:334 L:438
Weight	82kg
Surge Protection	SL35 Surge Limitor
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PAD0227 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 06/07/2026



