

Datasheet for: 3PHD05015

Product Type: 3P Isolating Delta Delta

5kva 3P Delta Delta 415v to 240v Hardwired



VA	5000
Input Voltage	415
Input Termination	3 way screw terminals
Input Current	6.96
amps	12.04
Output Voltage	240
Output Termination	3 way screw terminals
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	42kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	.04

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PHD05015 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 15/01/2025



[Handwritten Signature]

