

## Datasheet for: 3PHD05051

### Product Type: 3P Isolating Delta Delta

5kva 3P Delta Delta 415v to 208v Hardwired



|                    |   |
|--------------------|---|
| VA                 | 5000  |
| Input Voltage      | 415   |
| Input Termination  | Terminal Posts                              |
| Input Current      | 4   |
| amps               | 8   |
| Output Voltage     | 208   |
| Output Termination | Terminal Posts                              |
| Product Case       | P6 Industrial floor/wall mounting case IP23 |
| Dimension          | Ht:454 L: 384 W:305 (mm)                    |
| Weight             | 23kg  |
| Product Type       | Isolating transformer                       |
| Standard           | Conforms to EN61558-2-6 CE & RoHS           |
| Regulation         | .04   |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product 3PHD05051 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
03/09/2025

A handwritten signature in black ink, likely of the exporter or a representative of Airlink Transformers.