

Datasheet for: 3PHD07500

Product Type: 3P Isolating Delta Delta

7.5kVA 3P Delta Delta 230V to 440V Hardwired



VA	7500
Input Voltage	230
Input Termination	M5 Brass studs
Input Current	10.87
amps	5.7
Output Voltage	440
Output Termination	M5 Brass studs
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	26kg
Surge Protection	MS35 Surge Limiter
Product Type	Isolating transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Regulation	.04

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PHD07500 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/11/2024



[Handwritten Signature]

