



# Datasheet for: 3PHD20840

## Product Type: 3P Isolating Delta Delta

20kva 3P Delta Delta 230v to 400v Hardwired



VA	20000
Input Voltage	230
Input Termination	M8 Brass studs
Input Current	50.26
amps	28.9
Output Voltage	400
Output Termination	M8 Brass studs
Product Case	T3 Industrial floor/wall mounting case IP23
Dimension	Ht:500 L: 525 W:450 (mm)
Weight	135kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	.04

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PHD20840 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 04/07/2026



www.airlinktransformers.com - VAT No. 573 1888 10  
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | sales@airlinktransformers.com