

Datasheet for: 3PHD25453

**Product Type: 3P Isolating Delta Delta** 

25kva 3P Delta Delta 415v to 400v Hardwired



VA 25000 Input Voltage 415

Input Termination M8 Brass studs

Input Current 34.82 amps 36.13 Output Voltage 400

Output Termination M8 Brass studs

Product Case T3 Industrial floor/wall mounting case IP23

Dimension Ht:500 L: 525 W:450 (mm)

Weight 150kg

Product Type Isolating transformer Conforms to EN61558-2-6 CE & RoHS

Regulation .04

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PHD25453 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

15/12/2025

