

Datasheet for: 3PHD30915

Product Type: 3P Isolating Delta Delta

30kva 3P Delta Delta 415v to 240v Hardwired



VA	30000
Input Voltage	415
Input Termination	M12 Brass studs
Input Current	41.79
amps	72.25
Output Voltage	240
Output Termination	M12 Brass studs
Product Case	T4 Industrial floor/wall mounting case IP23
Dimension	Ht:600 L: 625 W:500 (mm)
Weight	160kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	.04

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
01/03/2021

