

## Datasheet for: 3PTS02773

### Product Type: 3P+N Isolating Delta Star

2.5kva 3P Delta Star 380v to 380v Hardwired



|                    |   |
|--------------------|---|
| VA                 | 2500  |
| Input Voltage      | 380   |
| Input Termination  | 3 way screw terminals                                   |
| Input Current      | 3.80  |
| amps               | 3.8   |
| Output Voltage     | 380   |
| Output Notes       | Line to Line 380v Line to neutral 220vac                |
| Output Termination | 3 way screw terminals                                   |
| Product Case       | P4 Industrial floor/wall mounting case IP23             |
| Dimension          | Ht:270 L: 338 W:215 (mm)                                |
| Weight             | 15kg  |
| Product Type       | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation         | 6.0%  |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS02773 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
06/05/2026



