

**Datasheet for: 3PTS05450**

**Product Type: 3P+N Isolating Delta Star**

5kva 3P Delta Star 415v to 480v Hardwired



|                    |   |
|--------------------|---|
| VA                 | 5000  |
| Input Voltage      | 415   |
| Input Termination  | 3 way screw terminals                                   |
| Input Current      | 6.96  |
| amps               | 6.02  |
| Output Voltage     | 480   |
| Output Notes       | Line to Line 480v Line to neutral 276vac                |
| Output Termination | 3 way screw terminals                                   |
| Product Case       | P6 Industrial floor/wall mounting case IP23             |
| Dimension          | Ht:454 L: 384 W:305 (mm)                                |
| Weight             | 42kg  |
| Product Type       | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation         | 5.5%  |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS05450 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
14/01/2025


