

Datasheet for: 3PTS05451

Product Type: 3P+N Isolating Delta Star

5kva 3P Delta Star 415v to 460v Hardwired



VA	5000
Input Voltage	415
Input Termination	3 way screw terminals
Input Current	6.96
amps	6.28
Output Voltage	460
Output Notes	Line to Line 460v Line to neutral 265vac
Output Termination	3 way screw terminals
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	42kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	5.5%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PTS05451 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 27/05/2026



