

Datasheet for: 3PTS11840

Product Type: 3P+N Isolating Delta Star

10kva 3P Delta Star 230v to 380v Hardwired



| | |
|--------------------|---|
| VA | 10000 |
| Input Voltage | 230 |
| Input Termination | M5 Brass studs |
| Input Current | 25.13 |
| amps | 15.21 |
| Output Voltage | 380 |
| Output Notes | Line to Line 380v Line to neutral 220vac |
| Output Termination | M5 Brass studs |
| Product Case | P6 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:454 L: 384 W:305 (mm) |
| Weight | 65kg |
| Product Type | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation | 5.0% |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/09/2019

