

# Datasheet for: 3PTS16349

## Product Type: 3P+N Isolating Delta Star

15kva 3P Delta Star 208v to 380v Hardwired



|                    |   |
|--------------------|---|
| VA                 | 15000   |
| Input Voltage      | 208   |
| Input Termination  | M6 Brass studs  |
| Input Current      | 41.69   |
| amps               | 22.82   |
| Output Voltage     | 380   |
| Output Notes       | Line to Line 380v Line to Neutral 220v                  |
| Output Termination | M6 Brass studs  |
| Product Case       | T3 Industrial floor/wall mounting case IP23             |
| Dimension          | Ht:500 L: 525 W:450 (mm)                                |
| Weight             | 95kg  |
| Product Type       | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation         | 4.5%  |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS16349 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 06/05/2026



