

Datasheet for: 3PTS25675

Product Type: 3P+N Isolating Delta Star

25kva 3P Delta Star 380v to 230v Hardwired



VA	25000
Input Voltage	380
Input Termination	M8 Brass studs
Input Current	38.03
amps	62.83
Output Voltage	230
Output Notes	Line to Line 230v Line to Neutral 132v
Output Termination	M8 Brass studs
Product Case	T3 Industrial floor/wall mounting case IP23
Dimension	Ht:500 L: 525 W:450 (mm)
Weight	150kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	3.5%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product 3PTS25675 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
09/09/2025

A handwritten signature in black ink, likely of the exporter or a representative of Airlink Transformers.