

Datasheet for: 3PTS25677

Product Type: 3P+N Isolating Delta Star

25kva 3P Delta Star 380v to 200v Hardwired

VA 25000 Input Voltage 380

Input Termination M8 Brass studs

Input Current 38.03 amps 72.25 Output Voltage 200

Output Notes Line to Line 200v Line to Neutral 115v

Output Termination M8 Brass studs

Product Case T3 Industrial floor/wall mounting case IP23

Dimension Ht:500 L: 525 W:450 (mm)

Weight 150kg

Product Type Isolating transformer Conforms to EN61558-2-6 CE & RoHS

Regulation 3.5%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PTS25677 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deaC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

15/12/2025



