

## Datasheet for: 3PTS36314

### Product Type: 3P+N Isolating Delta Star

35kva 3P Delta Star 380v to 240v Hardwired



|                    |   |
|--------------------|---|
| VA                 | 35000   |
| Input Voltage      | 380   |
| Input Termination  | M12 Brass studs   |
| Input Current      | 53.24   |
| amps               | 84.3  |
| Output Voltage     | 240   |
| Output Notes       | Line to Line 240v Line to Neutral 138v                  |
| Output Termination | M12 Brass studs   |
| Product Case       | T4 Industrial floor/wall mounting case IP23             |
| Dimension          | Ht:600 L: 625 W:500 (mm)                                |
| Weight             | 185kg   |
| Product Type       | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation         | 3.0%  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS36314 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
09/09/2025

