

Datasheet for: 3PTS42756

Product Type: 3P+N Isolating Delta Star

40Kva 3P+N Delta Star 380V to 220V Hardwired



VA	40000
Input Voltage	380
Input Termination	M12 Brass studs
Input Current	60.85
amps	105.1
Output Voltage	220
Output Notes	Line to Line 220v Line to Neutral 127v
Output Termination	M12 Brass studs
Product Case	T4 Industrial floor/wall mounting case IP23
Dimension	Ht:600 L: 625 W:500 (mm)
Weight	265kg
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	3.0%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PTS42756 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/04/2026



