

Datasheet for: 3PTS42763

Product Type: 3P+N Isolating Delta Star

40Kva 3P+N Delta Star 230V to 220V Hardwired



VA 40000 Input Voltage 230

Input Termination M12 Brass studs

Input Current 100.53 amps 105.1 Output Voltage 220

Output Notes Line to Line 220v Line to Neutral 127v

Output Termination M12 Brass studs

Product Case T4 Industrial floor/wall mounting case IP23

Dimension Ht:600 L: 625 W:500 (mm)

Weight 265kg

Product Type Isolating transformer Conforms to EN61558-2-6 CE & RoHS

Regulation 3.0%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PTS42763 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deaC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

13/12/2025



