

Datasheet for: 3PTSD20844

Product Type: 3P+N Isolating Delta Star

20kva 3P Delta Star 415v to 380v Hardwired



| | |
|--------------------|---|
| VA | 20000 |
| Input Voltage | 415 |
| Input Termination | M8 Brass studs |
| Input Current | 27.86 |
| amps | 30.42 |
| Output Voltage | 380 |
| Output Notes | Line to Line 380v Line to Neutral 220v |
| Output Termination | M8 Brass studs |
| Product Case | T3 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:500 L: 525 W:450 (mm) |
| Weight | 135kg |
| Product Type | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation | 4.0% |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PTSD20844 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/02/2025

