

Datasheet for: AL0052

Product Type: 3P+N Isolating Delta Star

15kVA 3P+N 440V to 440/254v Wired in Delta Star configuration
60Hz



VA	15000
Input Voltage	440
Input Termination	Terminals M6 Studs
Input Current	20.94
amps	20.94
Output Voltage	440
Output Notes	440V/254V
Output Termination	terminals M6 Studs
Product Case	T4 Industrial floor mounting case IP44
Dimension	Ht:450 W:450 L:600
Weight	120kg
Surge Protection	SL35 30A Surge Limitor
Product Type	Transformer Conforms to EN61558-2-6 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product AL0052 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
17/03/2025

