

## Datasheet for: AL0052

### Product Type: 3P+N Isolating Delta Star

15kVA 3P+N 440V to 440/254v Wired in Delta Star configuration  
60Hz



|                    |   |
|--------------------|---|
| VA                 | 15000   |
| Input Voltage      | 440   |
| Input Termination  | Terminals M6 Studs                            |
| Input Current      | 20.94   |
| amps               | 20.94   |
| Output Voltage     | 440   |
| Output Notes       | 440V/254V                                     |
| Output Termination | terminals M6 Studs                            |
| Product Case       | T4 Industrial floor mounting case IP44        |
| Dimension          | Ht:450 W:450 L:600                            |
| Weight             | 120kg   |
| Surge Protection   | SL35 30A Surge Limitor                        |
| Product Type       | Transformer Conforms to EN61558-2-6 CE & RoHS |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product AL0052 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
23/02/2025



