

Datasheet for: 3PAD0043

Product Type: 3P+PE Auto Delta Delta

2500VA 3P 415-380v Hardwired



VA	2500
Input Voltage	415
Input Termination	Screw terminals
Input Current	3.48
amps	3.8
Output Voltage	380
Output Termination	Screw terminals
Product Case	P2 Industrial floor/wall mounting case IP23
Dimension	Ht:223 W:152 L:220
Weight	5kg
Surge Protection	SL32 Surge Limiter
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
22/09/2019

