

## Datasheet for: 3PAD0064

### Product Type: 3P+PE Auto Delta Delta

5000VA 3P 460-380v Hardwired



VA	5000
Input Voltage	460
Input Termination	Screw terminals
Input Current	6.28
amps	7.6
Output Voltage	380
Output Termination	Screw terminals
Product Case	P2 Industrial floor/wall mounting case IP23
Dimension	Ht:223 W:152 L:220
Weight	10kg
Surge Protection	SL32 Surge Limiter
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
23/09/2019

