

**Datasheet for: 3PAD0065**

**Product Type: 3P+PE Auto Delta Delta**

5000VA 3P 400-200v Hardwired



|                    |  |
|--------------------|--|
| VA                 | 5000   |
| Input Voltage      | 400  |
| Input Termination  | Screw terminals  |
| Input Current      | 7.22   |
| amps               | 14.43  |
| Output Voltage     | 200  |
| Output Termination | Screw terminals  |
| Product Case       | P4 Industrial floor/wall mounting case IP23              |
| Dimension          | Ht:270 W:215 L:338                                       |
| Weight             | 27kg   |
| Surge Protection   | SL32 Surge Limitor                                       |
| Product Type       | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PAD0065 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
21/01/2025

