

Datasheet for: 3PAD0066

Product Type: 3P+PE Auto Delta Delta

5000VA 3P 380-200v Hardwired



| | |
|--------------------|--|
| VA | 5000 |
| Input Voltage | 380 |
| Input Termination | Screw terminals |
| Input Current | 7.6 |
| amps | 14.43 |
| Output Voltage | 200 |
| Output Termination | Screw terminals |
| Product Case | P4 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:270 W:215 L:338 |
| Weight | 27kg |
| Surge Protection | SL32 Surge Limiter |
| Product Type | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
22/09/2019

