

# Datasheet for: 3PAD0220

## Product Type: 3P+PE Auto Delta Delta

20kVA 3P 415-230v Hardwired



VA	20000
Input Voltage	415
Input Termination	Screw terminals
Input Current	27.84
amps	50.2
Output Voltage	230
Output Termination	Screw terminals
Product Case	P7 Industrial floor/wall mounting case IP23
Dimension	Ht:480 W:334 L:438
Weight	74kg
Surge Protection	SL35 Surge Limitor
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PAD0220 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
16/06/2026



