

## Datasheet for: 3PAD0221

### Product Type: 3P+PE Auto Delta Delta

20kVA 3P 400-230v Hardwired



|                    |  |
|--------------------|--|
| VA                 | 20000  |
| Input Voltage      | 400  |
| Input Termination  | Screw terminals  |
| Input Current      | 28.88  |
| amps               | 50.2   |
| Output Voltage     | 230  |
| Output Termination | Screw terminals  |
| Product Case       | P7 Industrial floor/wall mounting case IP23              |
| Dimension          | Ht:480 W:334 L:438                                       |
| Weight             | 74kg   |
| Surge Protection   | SL35 Surge Limiter                                       |
| Product Type       | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
11/04/2021

