

Datasheet for: AT1502

Product Type: Autowound Transformers

1500VA 0-120-230v



| | |
|--------------------|---|
| VA | 1500 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads fitted with screw terminal block |
| Output Voltage | 120 |
| Output Termination | 200mm Flexible leads fitted with 3way terminal block |
| Dimension | OD: 155 Ht: 70mm |
| Weight | 6kg |
| Product Type | Autowound transformer |
| Standard | Conforms to EN61558-2-13 CE & RoHS |
| Fixing | Fixing Potted centre drilled 10mm hole |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product AT1502 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
12/09/2025

A handwritten signature in black ink, likely of the company representative.