



Datasheet for: BT3231

Product Type: Boating Transformers

3600va 230v to 230v Isolating transformer for Boats to prevent Galvanic corrosion. Hardwired.

| | |
|--------------------|---|
| VA | 3600 |
| Input Voltage | 230 |
| Input Termination | TB03 3way screw terminal Medium 24A |
| Input Current | 16 |
| amps | 16 |
| Output Voltage | 230 |
| Output Termination | TB04 3way screw terminal Large 76A |
| Product Case | 801 Yellow Durable reinforced waterproof case IP67 |
| Dimension | Ht:355 L:320 W:355 (mm) |
| Weight | 21kg |
| Primary Protection | SP20 Push to reset circuit breaker |
| Surge Protection | SL35 30A Surge limiter |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |



Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product BT3231 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 14/02/2026



www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com