



Datasheet for: BT3240

Product Type: Boating Transformers

3600va 230v to 230v Isolating transformer Mains lead with 16amp plug Outlet:16amp Socket with MCB protection



| | |
|----------------------|--|
| VA | 3600 |
| Input Voltage | 230 |
| Input Termination | 10 meter mains lead with 16amp Blue CEE plug |
| Input Current | 16 |
| amps | 16 |
| Output Voltage | 230 |
| Output Termination | 2P+E 16amp panel mounting Blue socket |
| Product Case | 801 Durable reinforced waterproof case IP67 |
| Dimension | Ht:355 L:320 W:355 (mm) |
| Weight | 21kg |
| Primary Protection | SP20 Push to reset circuit breaker |
| Secondary Protection | MCB Protection |
| Surge Protection | SL35 30A Surge limiter |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-06 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product BT3240 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 27/05/2026

