

Datasheet for: BT3252

Product Type: Boating Transformers

3600va 230v to 230v Isolating transformer for Boats to prevent Galvanic corrosion



Input Termination TB03 3way screw terminal Medium 24A

Input Current 16 amps 16 Output Voltage 230

Output Termination TB04 3way screw terminal Large 76A
Product Case P6 Industrial floor/wall mounting case IP23

Dimension Ht:454 L: 384 W:305 (mm)

Weight 30kg

Primary Protection MCB 2P circuit breaker
Secondary Protection RCD 2P 16A 30ma
Surge Protection SL35 30A Surge limiter
Product Type Safety Isolating transformer

Standard Conforms to EN61558-2-6 CE & RoHS



Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product BT3252 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

25/11/2025

