



Datasheet for: BT5231

Product Type: Boating Transformers

5000va 230v to 230v Isolating transformer for Boats to prevent Galvanic corrosion

| | |
|----------------------|---|
| VA | 5000 |
| Input Voltage | 230 |
| Input Termination | TB04 3way screw terminal Large 76A |
| Input Current | 21 |
| amps | 21 |
| Output Voltage | 230 |
| Output Termination | TB04 3way screw terminal Large 76A |
| Product Case | P5 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:353 L: 350 W:242 (mm) |
| Weight | 36kg |
| Primary Protection | MCB 2P 25A |
| Secondary Protection | RCD 2P50A 30ma |
| Surge Protection | SL35 30A Surge limiter |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product BT5231 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/06/2026


