

Datasheet for: BT7230

Product Type: Boating Transformers

7500VA 230V to 230V with galvanic protection



VA 7500 Input Voltage 230

Input Termination M6 Brass Studs

Input Current 32 amps 32 Output Voltage 230

Output Termination M6 Brass studs

Product Case P6 Industrial floor/wall mounting case IP23

Dimension H:454, L:384, W:305,

Weight 45kg
Primary Protection 32A MCB
Secondary Protection 32A RCBO

Surge Protection MS35 Surge Limiter

Product Type Safety Isolating transformer

Standard Conforms to EN61558-2-06 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product BT7230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

15/12/2025

