



Datasheet for: BT7230

Product Type: Boating Transformers

7500VA 230V to 230V with galvanic protection

VA	7500
Input Voltage	230
Input Termination	M6 Brass Studs
Input Current	32
amps	32
Output Voltage	230
Output Termination	M6 Brass studs
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	H:454, L:384, W:305,
Weight	45kg
Primary Protection	32A MCB
Secondary Protection	32A RCBO
Surge Protection	MS35 Surge Limiter
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-06 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product BT7230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
04/12/2024



